



# SLINGS AND CRADLES

Mathey Dearman's Pipe Cradles and Slings are an effective way to move pipe, specifically designed for pipeline installation projects. Mathey Dearman currently offers cradles from 2" - 36" and all are equipped with 4 inch urethane "round cut" wheels with sealed anti-friction bearings. All spreader bar designs are third party tested and comply with industry standards. These models are equipped with 5/8" wire rope and all rope is swaged and certified.

## Features and advantages

- Durable 95a urethane coating designed for multiple uses
- Sealed anti-friction bearings
- Measures 4" tread width x 4.5" diameter
- 5/8" wire rope, swaged
- Machined hub for smooth wheel rotation



2001



2002



2003



2004

Sealed bearing wheels with protective metal end flange. Great urethane replacement roller for most other brands. 4" x 6" with radius cutout for pipe shape and designed for 5/8" wire rope.

4" Roller  
PN 90024



| ITEM NUMBER | DESCRIPTION                      | LOAD CAPACITY           |
|-------------|----------------------------------|-------------------------|
| 2001-3      | Roller Sling 2" - 8"             | 1,300 kg / 3,000 lbs.   |
| 2001-4      | Roller Sling 2" - 12"            | 1,300 kg / 3,000 lbs.   |
| 2001-5      | Roller Sling 2" - 18"            | 1,300 kg / 3,000 lbs.   |
| 2001-7      | Roller Sling 2" - 24"            | 1,300 kg / 3,000 lbs.   |
| 2002        | 2 Strand Roller Cradle 6" - 12"  | 7,710 kg / 17,000 lbs.  |
| 2003        | 2 Strand Roller Cradle 12" - 24" | 7,710 kg / 17,000 lbs.  |
| 2004        | 4 Strand Roller Cradle 12" - 24" | 12,700 kg / 28,000 lbs. |
| 2005        | 2 Strand Roller Cradle 24" - 36" | 12,813 kg / 28,250 lbs. |
| 2006        | 4 Strand Roller Cradle 24" - 36" | 25,700 kg / 56,500 lbs. |

